



GN 191.1
Aluminum / Stainless Steel


T-Angle linear actuator connectors
for linear actuators Ø18













Inox Stainless Steel

3 Identification no.

2 with 2 Stainless Steel-Clamping screws DIN 912

1 d_1 Bore B **without** slide insert	d_1 Bore G **with** slide insert	2 d_2 Clamping bore B	d_3 Clamping thread	d_4 Mounting screw on the follower	k_1 Clamping length	k_2 Clamping length	Length **l**	**m**	Clamping kit for d_3 Lever zinc die casting	Lever Stainless Steel
B 18*	G 18	B 18	M 6	M 3	25	25	61	39	GN 911-M6-22	GN 911.3-M6-22

* only available in version SW

Specification

4

- Aluminum plastic coated black, RAL 9005, textured finish ● **SW**
- Stainless Steel AISI CF-8 **NI**
  - matte shot-blasted
  - only with slide insert
- Guide bores / Clamping bores mechanically machined
- Slide insert Plastic (PA / PTFE)
- Socket cap screws DIN 912 Stainless Steel AISI 304
- Hexagon nuts DIN 985 Stainless Steel AISI 304
- *Stainless Steel characteristics* → *Page 1489*
- *Plastic characteristics* → *Page 1483*
- RoHS

Accessory

- Clamping kits GN 911 / GN 911.3 → *Page 1242*

Information

GN 191.1 T-angle linear actuator connectors are normally supplied **mounted** only in connection with a linear actuator and for function control.

By means of the clamping screw on the guide bore d_1 the movement can either be set or the linear actuator connector can be clamped (after setting of final adjustment).

The standard version of the clamping screws are socket cap screws with hexagonal socket DIN 912. They can be replaced by clamping kits GN 911 / GN 911.3 (article code see table of dimensions).

see also...

- *Construction tubes GN 990* → *Page 1277*
- *Linear actuators GN 291* → *Page 1326*
- *Linear actuators GN 292* → *Page 1328*

How to order (Aluminum)

1 2 3 4
GN 191.1-G18-B18-2-SW

1	d_1
2	d_2
3	Identification no.
4	Finish

How to order (Stainless Steel)

1 2 3 4
GN 191.1-G18-B18-2-NI

1	d_1
2	d_2
3	Identification no.
4	Material