



ROSTFREI
Inox
Stainless
Steel

3 Type

- E with threaded blind bore
- D with threaded through bore
- C with plain blind bore H7

1 d_1	2 d_2 Thread Type E	Type D	2 d_3 H7 Bore Type C	d_4	$h_1 \approx$	$h_2 \approx$	t_1 min.	t_2
32	M 5	-	-	12	21	12	10	-
32	M 6	M 6	B 6	12	21	12	12	10
40	M 6	-	-	14	26	14	12	-
40	M 8	M 8	B 8	14	26	14	15	13
50	M 8	-	-	18	33	19	15	-
50	M 10	M 10	B 10	18	33	19	18	16
60	M 10	-	-	20	41	23	18	-
60	M 12	M 12	B 12	20	41	23	22	20

Specification

- Stainless Steel precision casting
 - AISI CF-8
 - matt shot-blasted
 - highly polished (only Type D and E)
- Cross hole GN 110 → Page 1127
- ISO-Fundamental Tolerances → Page 1132
- Stainless Steel characteristics → Page 1144
- RoHS compliant

4 Information

MT
PL

Stainless Steel-Triangular knobs GN 5339.5 have been specially designed for use on machinery in the food industry. The smooth and enclosed areas as well as the corner radii comply with the requirements of hygiene standards.

Original ELESA-Design, manufactured in metal version under permission of ELESA s.p.a.

see also...

- *Stainless Steel-Star knobs GN 5334* → Page 288
- *Stainless Steel-Knurled nuts GN 536* → Page 321

How to order	1 d_1
	2 d_2 (d_3)
GN 5339.5-50-M8-E-MT	3 Type
	4 Finish